

IOBAC TAB-IT® FLOORING INSTALLATION SYSTEM SUPPORTING RE-USE

TECHNICAL DATASHEET

PRODUCT DESCRIPTION

Ultra thin, double-sided dry-tack tabs, IOBAC Tab-It cleanly and securely affixes carpet tiles, +4mm Luxury Vinyl Tiles (LVT), and woven vinyl tiles onto most common prepared sub-floors, including:

- non-metal raised access floors including calcium sulphate, aluminium and wood
- concrete/polished concrete
- wood
- ceramic
- vinyl/lino/VCT

Ultra Thin, Yet Super Strong:

Using the same proven dry-tack chemistry as IOBAC MagTabs®, Tab-It securely holds floor coverings in place with amazing grab force. Super strong, tear resistant material.

Extremely thin profile means no transference through to the flooring top surface.

Clean Removal for Easy Flooring Reuse:

Floor tiles are uplifted cleanly and easily for reuse or recycling via flooring manufacturers' take-back schemes.

The sub-floor is left contamination-free and ready for the next flooring installation straight away. Minimal work is needed to restore the sub-floor for the next install.

PRODUCT PERFORMANCE

- Highly shear resistant
- Good resistance to extremes of moisture and temperature, and ageing
- Chemical resistant
- Working temperature of +15 to +40°C
- Store between +10°C and +20°C



For Use in Common Built Environments

Fast, clean dry-laid installation process suitable for most common sub-floors.

Eliminates messy wet trades and VOC's associated with adhesive-based methods.



IOBAC TAB-IT® FLOORING INSTALLATION SYSTEM SUPPORTING RE-USE

TECHNICAL DATASHEET

PRODUCT COMPOSITION

Ultra thin, double-sided dry-tack tabs, double-lined for ease of installation



FLOOR COVERING:

Carpet tile, +4mm Luxury Vinyl Tile (LVT) or woven vinyl tile



ULTRA THIN ADHESIVE FILM LAYER (Flooring Side)

- Acrylic based adhesive with liner
- Odourless 100% solid material - VOC content not applicable

TEAR RESISTANT LINER

ULTRA THIN ADHESIVE FILM LAYER (Base Side)

- Acrylic based adhesive with liner
- Odourless 100% solid material - VOC content not applicable

PREPARED SUB-FLOOR

Non-metal raised access flooring, Concrete, Wood, Ceramic, Vinyl/lino/VCT

DIMENSIONS AND PACKAGING

Tab-It Dimensions:

- Each Tab-It is 97 x 97 mm
- ~ 0.1mm thickness

Packaging:

- 100 x Tab-It per roll
- 27 rolls per case
- = 2,700 x Tab-It per case

Case dimensions:

- 354 x 354 x 354 mm
- circa 13.5kg weight

INSTALLATION GUIDELINES

Preparation: Ensure sub-floor is clean, dry and free from loose particles which may impair grab.
If the subfloor has excessive laitance or dust, it may require a suitable primer or sealant prior to using Tab-It.
For full instructions, please refer to IOBAC Tab-It Installation guidance at iobac.com/tabit

Manufactured by Circular Building Solutions Ltd
Unit 9, Berry Court Farm, Bramley Road, Tadley, RG26 5AT
Email: info@circularbuildingsolutions.co.uk
Telephone: +44 (0)7703 132494